

ReTac®

Clear PET

ReTac® Clear PET is a 3 mil (75µ) clear printable polyester film coated on one side with ReTac® ultra removable adhesive, protected by a siliconized kraft release paper. ReTac® Clear PET offers a sustainable solution suitable for latex and UV printing, that can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- IDEAL FOR EASY TO APPLY RETAIL AND POP WINDOW GRAPHICS, NO WET INSTALL NEEDED
- RETAC CLEAR PET IS A NON-PVC SOLUTION, OFFERING A MORE ENVIRONMENTALLY FRIENDLY OPTION TO SATISFY THE RISING DEMAND FOR SUCH PRODUCTS FROM ALL CORNERS OF THE MARKET

Installation Recommendations:

Dry installation is recommended. Please refer to the ReTac Clear PET Application Guide for more details.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film	Gloss Clear Polyester (PET)
Adhesive	Clear ReTac® ultra removable and repositionable adhesive technology
Release Liner	135gsm one side siliconised clay coated kraft

PRODUCT CHARACTERISTICS

Film Thickness	3.0 mil (75µ)	3.7 mil
Adhesive Layer	0.7 mil (18µ)	(93µ)
Outdoor Durability	5 Years; 2 Years Removability (Ink Dependant)	
Application Temperature	>41°F (5°C)	
Service Temperature Range	40°F to 120°F (4.4°C to 48.9°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	



www.drytac.ch
hello@drytac.ch

talicq
IMAGING
Tel. 041 525 34 34

Talicq SA
Renglochstrasse 34
6012 Obernau
info@talicq.com
www.talicq.com